

**In the Claims**

Claims 1-20 remain in the application and are listed as follows:

1. (Original) A method of processing media content, the method comprising:

generating a motion compensated prediction of a region of media content;  
receiving an indication of whether there are first and second quantities of residual samples remaining for refining the prediction, on a per-region basis; and  
adding of the first quantity of residual samples to the prediction to generate a refined prediction value, when so indicated; and  
subtracting the second quantity of residual samples from the refined prediction value to generate a final representation, when so indicated.

2. (Original) A method according to claim 1, wherein the first and second residual samples are eight-bit signed samples.

3. (Original) A method according to claim 1, further comprising performing an inverse discrete cosine transformation of a decoded transform-domain representation of a total residual difference to be added to the motion compensated prediction for the region of media content.

4. (Original) A method according to claim 1, wherein the encoded region of media content is a block or macroblock of a frame of received media content.

1           5.     (Original) A method according to claim 1, wherein generating a  
2 prediction of media content is performed by a graphics processing accelerator  
3 under the control of a decoder application that is executing on a host computing  
4 system.

5  
6           6.     (Original) A method according to claim 1, further comprising:  
7           sending any prediction control information necessary for generation of a  
8 motion compensated predicted region to an accelerator,  
9           sending an indication to the accelerator of whether the first and second  
10 quantities of residual samples are to be applied, and  
11           sending the first and second sets of residual samples to the accelerator when  
12 indicated;  
13           performing subsequent processing and/or rendering at the accelerator.

14  
15           7.     (Original) A method according to claim 1, wherein the region is a  
16 block or macroblock of a frame of media content.

17  
18           8.     (Original) A storage medium comprising a plurality of executable  
19 instructions including a subset of which that, when executed, implement a method  
20 according to claim 1.

21  
22           9.     (Original) A computing system comprising:  
23 a storage medium including a plurality of executable instructions; and  
24  
25

1 an execution unit, coupled to the storage medium, to execute at least a  
2 subset of the plurality of executable instructions to implement a method according  
3 to claim 1.

4  
5 10. (Original) A storage medium comprising a plurality of executable  
6 instructions which, when executed, implement a decoder of media content to  
7 generate a motion compensated prediction of at least a region of media content, to  
8 receive an indication of one or more sets of samples of residual information to  
9 further refine the prediction, and to add a first set of such samples to the prediction  
10 to generate a modified prediction, if indicated, and to subtract a second set of such  
11 samples from the modified prediction to generate a final motion compensated  
12 prediction of the region, if indicated.

13  
14 11. (Original) A storage medium according to claim 10, wherein the  
15 executable instructions on the storage medium cause prediction control  
16 information necessary for generation of the motion compensated prediction and  
17 the indications of whether the first and/or second quantity of residual samples are  
18 to be applied and the actual first and second sets of residual samples to be sent to a  
19 communicatively coupled accelerator for subsequent processing and/or rendering.

20  
21 12. (Original) A storage medium according to claim 10, wherein the  
22 region of media content is a block or macroblock of a frame.

1 13. (Original) A storage medium according to claim 10, wherein the first  
2 and second residual samples are eight-bit signed samples.

3  
4 14. (Original) A storage medium according to claim 10, further  
5 comprising performing an inverse discrete cosine transformation of a decoded  
6 transform-domain representation of a total residual difference to be added to the  
7 motion compensated prediction for the region of media content.

8  
9 15. (Original) A computing system comprising:  
10 a decoder application to receive a region of media content and control  
11 generation of decoded media content; and  
12 an application program interface (API), communicatively coupling the  
13 decoder application with a hardware accelerator, wherein if the API receives an  
14 indication of one or more sets of residual samples, the first set of samples is added  
15 to a motion compensated prediction to generate a refinement of a prediction value,  
16 when so indicated, and a second set of samples is subtracted from the refined  
17 prediction value to generate a final representation, when so indicated.

18  
19 16. (Original) A computing system according to claim 15, further  
20 comprising:  
21 an accelerator, communicatively coupled to the decoder application via the  
22 API, to receive control and residual data information for subsequent processing  
23 and/or rendering.

24  
25

1           17. (Original) A computing system according to claim 15, wherein the  
2 decoder application generates the residual data samples utilizing an inverse  
3 discrete cosine transformation of a decoded transform-domain representation of a  
4 total residual difference to be added to the motion compensated prediction for the  
5 region of media content.

6  
7           18. (Original) A computing system according to claim 15, wherein the  
8 region of media content is a block or macroblock of a frame.

9  
10          19. (Original) A computing system according to claim 15, further  
11 comprising:

12           a storage medium comprising a plurality of executable instructions; and  
13           an execution unit, coupled to the storage medium, to execute at least a  
14 subset of the plurality of executable instructions to implement the API.

15  
16          20. (Original) A computing system according to claim 19, wherein the  
17 execution unit executes at least a subset of the plurality of executable instructions  
18 to implement the decoder application.